

## General Description:

AQUAWOOD FILLER is based on acrylic dispersion resin and selected filler, it is developed to patch – up uneven surface of the wood and to fill nail heads, and cracks.

## Major Uses:

AQUAWOOD FILLER is intended to fill cracks, knot holes and all blemishes of natural and synthetic wood. It is recommended for interior and exterior application.

## Characteristics and Physical Properties:

Appearance	Paste
Specific weight	1.5
Odour	Characteristic
Solid content (w)	75%
VOC	250 g/l
Colours	Natural Teak Mahogany Oak Dark oak Walnut Ebony

## Method of Application:

- The surface must be sanded and should be clean and free from any contaminants.
- Fill the holes and cracks by scraper or putty knife evenly.
- If the material is dry, add a little water to get required consistency.
- AQUAWOOD FILLER should be sanded and stained with appropriate dye or stain prior to the application of NC, PU or Acrylic topcoats.

## Storage:

AQUAWOOD FILLER should be kept in a cool area below 25<sup>0</sup>C. Keep in tightly closed container.

## Cleaning of Tools:

All tools should be cleaned with water.

## Packing:

Available in 500 ml., 1 lit, 4 lit.

## Physiological Hazards:

AQUAWOOD FILLER does not contain dangerous solvents, nevertheless, good ventilation in working area is recommended as well as the use of safety tools and equipment. AQUAWOOD FILLER is harmful if swallowed. If contact with eyes or skin occurs, wash well with fresh water and seek immediate medical advice.