GULF FALCON LACQUER THINNER

General Description:

N.C. LACQUER THINNER is a mixture of esters,

glycol, alcohol, and aromatic solvents suitable to all nitro products.

Advantages:

- 1. Quickly reduces the consistency of the lacquer to the required degree.
- 2. Improves film smoothness of lacquers when applied either by spray or dipping thus extending excellent finish.
- Lacquer dries without blushing, resin blush, pin holing and other surface defects.
- No "orange peel" developed after the evaporation of N.C. Lacquer Thinner, and therefore increases the tensile strength of the film along with its gloss

Characteristics:

Appearance	Visual	Clear
Specific weight	ASTM D 1475	0.85 kg/L
Colour (Saybolt)	ASTM D 1209	+30
Boiling point	ASTM D 850	56ºC
Acidity	ASTM D 1316	<0.03%
Non-aromatics		40%
Flash point	IP 170	10ºC

Note:

The contents of the aforementioned containers are of industrial use only by professionals.

Properties:

N.C. LACQUER THINNER has an average evaporation rate suggested for all Nitro Products when application is made in normal condition of temperature and humidity.

N.C. LACQUER THINNER has a certain action preventing milky effect of the surface.

Storage:

Keep the container tightly closed. Shelf life is unlimited in close container. Keep away from direct sunlight and other sources of heat or ignition

Packing:

Available in USG, 14 Irt and 18ltr (Pail).

Physiological Hazards:

cotains highly flammable solvents. lt Harmful if inhaled and if absorbed through skin can cause irritation.Always use protective gloves and eyegoggles when handling this product. lt highly is recommended to provide proper ventilation on working area. Keep out of reach of children. If contact with skin or splash in eyes, wash with fresh water for couple of minutes while а removing contaminated clothing and shoes. If affected by inhalation of vapour, remove to fresh air. If swallowed call a physician immediately

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.