



Thinners

InnoColor Thinners

Product Description

Used to reduce application viscosity and to increase the smoothness of the paint film. Thinner with high dissolving ability, compatible with InnoColor primers, basecoats, topcoats and clears.

 $IC-940\ Thinner\ 5^{\circ}C-15^{\circ}C\ (Fast) \qquad IC-950\ Thinner\ 15^{\circ}C-25^{\circ}C\ (Standard) \qquad IC-960\ Thinner\ 25^{\circ}C-35^{\circ}C\ (Slow)$

IC - 970 Thinner >35°C (Extra Slow)

Technical Characteristics

Color: Transparent Shelf life: 48 months at 25°C

Pre-treatment

As specified in the TDS of the products in which IC Thinner is being used.



Mixing Ratio

Stir well before use.

 IC - 981 Primer
 100 (vol)
 100 g

 IC - 961 Hardener
 25 (vol)
 20 g

 IC - 940/950/960/970 Thinner
 50 - 60 (vol)
 30 - 35 g

2K Solids/Clears 100 (vol) 100 g

IC - 940/950/960/970 Thinner depending on 2K Solids/Clears



Mixing Ratio

1K Basecoats

100 (vol) der

depending on colors

IC - 940/950/960/970 Thinner 100 - 120 (vol)

Mix well and strain before application.

Note: If the temperature and humidity are too high, IC - 70 retarder solvent can be added.



Application

As specified in the TDS of the products in which IC Hardeners are being used. **Important:** Due to different dissolving ability, it is recommended InnoColor products should be used with IC Thinner to ensure the best performance.

Tips:

- 1) Be cautious of over dissolution of the paint when using high dissolving thinner. Avoid orange peel.
- 2) Be cautious of under dissolution of the paint when using poor dissolving thinner. Avoid poor leveling and poor color effect (e.g. orientation of aluminum/pearl particles, poor solid color brightness).

The products are suitable for professional use only. The data contained in this publication are based on our current knowledge and experience. Youcan obtain the latest version of technical date sheet from our website at www.wonder-global.com or directly from your supplier.