



# Technical Data Sheet

## Levis Gold

Product Code – F97LVGOLD

### Product Description

Levis Gold is a solvent based, Metallized paint which is Gold in colour.  
Designed for interior use only.

### Advantages

Excellent decorative interior product with strong Gold metallized appearance, for use on woodwork, metal frames and wall surfaces.

### Typical Uses

Levis Gold can be applied to woodwork & Derivatives, plaster & derivatives, as well as ferrous and non-ferrous metals. Surfaces should be treated with an appropriate primer or coated over, old, clean and de-polished surfaces.

### Technical

Colours	Gold
Finish	Metallized Finish, Semi-Gloss
Volume Solids % $\pm$ 2%	38 $\pm$ 2%
Typical WFT (microns)	26
Typical DFT (microns)	10
Theoretical Spreading Rate m <sup>2</sup> /lt	16 - 20 m <sup>2</sup> / litre (Dependent on Substrate, Application Method, Application Conditions and System)
Specific Gravity	1.18 $\pm$ 0.02
Pack Sizes	0.125 LT, 0.250 LT, 0.500 LT, 0.750 LT
Flash Point	Above 34°C
VOC	716 Gms/Ltr
Storage	Store away from sunlight in a covered, cool and dry environment
Shelf Life	2 Years

### Drying/Over coating Information

°C	Touch Dry	Hard Dry	Overcoating
@ 25°C	30 Min	1 Hr	1 - 4 Hrs*

\* Product should be applied in 1 coat, if over coating is required please do so within these times.

### Application and Use

#### Application Methods

Brush	Use a Natural bristled Brush
Spray:	Use a Medium Pile Polyester Roller for Smooth Conventional Spray

### Thinner

For Mixing	Ready for use.
For Cleaning	Use Thinner 8300896

### Spray Recommendations

Conventional	Yes
Airless Spray	No



# Technical Data Sheet

## Levis Gold

Product Code – F97LVGOLD

### Surface Preparation

New uncoated surfaces

The surface to be primed should be well cured. Ideally the moisture content of the substrate should be less than 16% with a pH between 8 & 9.

Previously coated

The surface to be painted should be free from dust, grease, oil and should not be flaky. Primer is required only where the previously painted surface is removed, exposing the bare surface. In areas where multiple coats from previous applications are present, it is best to remove coatings to come to the barest surface possible. In case the surface is infested with mould or fungus thorough cleaning followed by treatment with an anti-fungal solution is recommended. The surface treated for the fungus or moulds should be thoroughly washed, dried and mopped prior to application

Special Surfaces

In cases where the surface temperature exceeds 35° C, wet the surface with water prior to application of primer, allowing sufficient time for the water to dry leaving the surface moist.

### Health Safety & environment

Store can upright with lid tightly closed in a dry area with good ventilation away from ignition sources. Keep out of reach of children and away from food and drink. Do not use empty paint containers to store food. Harmful if ingested. If ingested seek immediate medical attention. Do not breathe spray mist or dust from sanding. Use appropriate protection. In case of contact with eyes, rinse immediately with clean water and if irritation persists, seek medical attention. Avoid contact with skin by using appropriate protection. Contact with skin can cause irritation. Splashes can be removed from skin by using soap & clean water. Do not pour left over paint down drains or into watercourses. Dispose of empty containers as per local regulations. Material Safety datasheet can be made available on request.

*Disclaimer: The information in this data sheet is not intended to be exhaustive: any person using the product for any purpose other than that specifically recommended in this data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at their own risk. All advice given or statements made about the product (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability at all for the performance of the product or for (subject to law) any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our Conditions of Sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is liable to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to check with their local AkzoNobel Oman SAOC representative that this data sheet is current prior to using the product.*