

General Description:

WALL & WOODEN PUTTY is a vinyl acrylic-based putty filler that gives excellent filling properties and smooth finish. It is easy to sand and perfectly formulated for interior walls.

Advantages:

- For interior and exterior use.
- Good adhesion properties.
- Good sandability.
- Good drying properties.
- Ease of application.
- Non – toxic and environment friendly.

Characteristics and Physical Properties:

Colour	White
Gloss	Matt
Specific Gravity	1.75 +/- 0.05Kg. / lit.
Volume solids	52%
Coverage	5 - 7 m ² / lit.
Touch Dry	1 – 2 hrs.
Sanding	6 – 8 hrs.

Surface Preparation:

New Substrates:

- Substrate must be free from any form of contaminants.
- Apply 1 – 2 coats of MAS Masonry AR Primer and MAS Masonry Primer White into the substrate.
- Application of BYT WALL & WOODEN PUTTY to smoothen the surface. Application of 1 – 2 coats of MASCRYL # 1000 or Mastic Royal for final top coating.

Old Concrete (previously painted)

- Remove all blistered, cracked and peeled off paint from the surface.
- Penetrated paint must be cleared and treated with 3% ammonia and water.
- Glossy finish coat must be sanded.
- Apply 1 coat of masonry primer prior to application of WALL & WOODEN PUTTY with a rate of 0.5 – 1.0 kg/m² depending on the porosity of the surface.

Method of Application:

Method of Application: - Putty Knife

Instruction for use	
Recommended Thinner	- Sweet Water.
Volume of Thinner	-approx. 0-5%
For cleaning	-Sweet Water.

Storage:

The product must be stored in accordance with national regulations. The product should be kept in a cool and well ventilated place, protected from heat and direct sunlight. Contents must be kept tightly closed.

Cleaning of Tools:

All tools should be cleaned with water.

Packing:

Available in 1Usg. and 5 Usg. (Pail)

Precautions:



See Safety Indication Sheet.