



GOLD PAINT

General Description:

GOLD PAINT is a brilliant, super resistant gold solution based on selected resin with selected gold powder. It is fast drying with exceptional long lasting effect.

Major Uses:

High recommended for all decorative works on wood, metal, plaster, concrete, precast, old paint and false ceiling.

Characteristics and Physical Properties:

Colour	Gold
Specific Gravity	1.0
Solid Content	30%
Coverage	25 – 28 m ² / lit.
Flash point`	20 ⁰ C
Dry	3 hrs.
Recoat	12 hrs.

Application Details:

Method of application	By brush, roller or spray
Dilution	Not required
Mixing Ratio	Single pack

Surface Preparation:

Steel:

If sandblasting is not possible, wire brushing is recommended. The surface should be cleaned, free from dust, oil, grease and other contaminants.

Wood:

Substrate should be primed with suitable primer prior to the application of GOLD PAINT

Storage:

GOLD PAINT should be kept in cool area below 25⁰C. Keep tightly closed container

Cleaning of Tools:

All tools should be cleaned with Wash Thinner as soon as possible.

Packing:

Available in 1Usg, 1 lit, ½ lit, 250ml, 125ml.

Physiological Hazards:

GOLD PAINT does not contain dangerous solvents, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment. GOLD PAINT is flammable and harmful if swallowed. If contact with eyes or skin occurs, wash well with fresh water and seek immediate medical advise..

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.