



P50 TEX FIBERGLASS PUTTY

Fiberglass filler

A) DESCRIPTION AND FIELDS OF APPLICATION:

Special filler reinforced with fiberglass. Easy sanding. Used to repair holes and other big imperfections of sheet metal and glass fiber panels.

B) TECHNICAL DATA:

Composition	Unsaturated polyester resin, fiberglass and mineral charges
Specific weight	1.48 ± 0,1 kg/l
Available colours	Grey
Safety data	See safety data sheet

C) SURFACE PREPARATION :



* Iron, steel plate, glass fiber reinforced plastic

* Original paints or aged topcoat finishes



* Clean well the surface to be treated with V09 Antisil. Make sure it is dry and free from silicone, wax, grease and any extraneous material.

* On base coats or enamel top coats, sand and clean the surface before applying the filler.

D) CAUTIONS:

* Mix well the filler with 1-3 % hardener. Do not exceed with the hardener to avoid risk of staining during painting operations.

* Do not utilize the product at temperatures below 5°C.

* Store in a cool and dry place.



E) PROCESSING:



1-3% C10 paste hardener pot life 5-7' at 20°C



application with putty knife



<30' at 20°C



4-5' at 1 m.



P40-P80 roughing-out

F) TOOLS CLEANING:

* With nitro thinner

G) RECOATING :

S40 Standard grigio
S48 Special rosso
S71 Flex grigio S
S27 Leggero
S49 Universale ZN

Technical indications and advices are based on our own experiences. We assure the perfect quality of products. However, being the utilization out of our control, we assume no responsibility on the results obtained