POLIKOR STONE CHIP PROTECTOR



Polikor Stone Chip Protector is a special air drying synthetic resin based rubber reinforced impact protection product.

General Properties

It provides fast drying with a perfect adhesion. Protects the surface from corrosion, oil, salt, water and humidity. Provides good sound proofing. It does not contain bitumen, wax or asphalt. It forms a strong flexible film with high stone chip resistance for underbody protection of vehicles.

Colour	: Black / Grey / White
Density(20 °C)	: 1,52 ± 0,05 g/cm ³

Application Surfaces

It is specially produced againts stone chipping on undercoatings of automobiles and commercial vehicles. It can be coated with all paint systems.

Application



The surface to be applied is sanded and then degreased with a cleaning solvent.



Wait for the complete drying to overcoat.



Shake well before opening. Apply with a suitable under body spray gun.



Wear respiratory protection during application.

Storage



Polikor Stone Chip Protector should be kept in its original can in a cool place with the lid securely closed. Under suitable conditions, it can be stored for one year at temperatures up to 25 °C. Improper storage conditions shorten the shelf life of the product.

Caution



For professional use only. Make applications where ventilation is sufficient. Keep away from heat, sparks, flame, hot surfaces. Vapours may cause flash fire. Causes eyes and skin irritation. Do not breathe vapours. Use required personal protective equipment. In case of contact with eyes or skin, rinse immediately with plenty of water. For more information see the SDS.

The information on this TDS is based on present knowledge and experience. The user is responsible for taking the mentioned precautions and having full and complete knowledge of the use of the product.

POLIKOR BOYA VE KİMYA SANAYİ TİCARET A.S. İzmir Yolu Cad. No:692 16370 Nilüfer - BURSA / TURKEY T + 90(224) 449 02 20 - F + 90(224) 449 02 27 polikor@polikor.com - www.polikor.com



