



TURPENTINE

General Description:

TURPENTINE is a clear, colourless hydrocarbon liquid.

Major Uses:

TURPENTINE is recommended for synthetic enamel and for air-drying varnishes and lacquers.

Characteristics:

Appearance		Clear liquid
Specific Gravity	ASTM D 3505	0.78 Kg. / lit.
Colour (Saybolt)	ASTM D 1209	+30
Initial Boiling Point	ASTM D 850	130 ⁰ C.
Copper Corrosion	ASTM D 849	none
Non – Aromatics	ASTM D 2360	> 80%
Flash Point (Abel)	IP 17	30 ⁰ C

Properties:

TURPENTINE has an average evaporation rate suggested for all alkyd Products when application is made in normal condition of temperature and humidity. TURPENTINE has a certain action preventing milky effect of the surface.

Keep the container tightly closed. Shelf life is unlimited in close container. Keep away from direct sunlight and other sources of heat or ignition; do not smoke in storage areas.

Packing:

Available in 4 lit (Usg), 20 lit (Pail) and 200 lit (Drum)

Physiological Hazards:

TURPENTINE contains flammable solvents. Always use protective gloves and eye goggles when handling this product. It is recommended to provide proper ventilation on working area. If contact with skin or splash in eyes, wash with fresh water and seek medical assistance.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.