

THINNER 222

TECHNICAL DATA SHEET

Product Description

THINNER CODE: 222

is fast drying, very good solvency and economical thinner for general purpose use. It is good cleaning, washing and thinning paint and related product. A wide range of packing is available. For 2K car paints.

Suitability for use

Products that will tolerate thinning with Thinner 222 are as followed:

- To be used to dissolve Clear coat, Hardener, Acrylic and Basecoat paints Stoving Enamel
- To be used as a dissolver for wood stains

for the best finish and drying for products we recommend using suitable Thinner . Thinner 222 should not be used in other products without prior confirmation of its suitability from the manufacturer.

TYPICAL PHYSICAL PROPERTIES

APPEARANCE	Colorless
BOILING POINTS@760 mm Hg	84 °C ±2
MELTING POINT	-92 °C
FLASH POINT (Tag Closed Cup)	12 °C
SPECIFIC GRAVITY 25 °C /25 °C	0.84 ±2

Availability

All packages are available .

Storage and Shelf Life

The flash point of Thinner 222 is below 9°C. Store in a dry place at a temperature of 10 – 30°C and in accordance with the Highly Flammable Liquids and Liquefied Petroleum Gases Regulations.

Health and Safety

This material is for Professional Use Only and the user is required to comply with the appropriate Health & Safety Regulations. Refer to the Material Safety Data Sheet for Health and Safety information.

Disclaimer:

The information contained in these pages is not intended to be exhaustive, and all persons using the product without first obtaining confirmation from Petra paints Factory co. as to the suitability of the product for the intended use, does so at their own risk. Whilst every effort is made to ensure the information given about the product (whether in this sheet or otherwise) is correct, we have no control over the quality or condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree to do so, we do not accept any liability, whatsoever or howsoever arising from the performance of the product or for any loss or damage (other than death or personal injury resulting from our negligence) arising out of use of the product. All information contained in this sheet is liable to modification from time to time and we reserve the right to change the product in accordance with our policy of continuous product development.