



THINNER SH

General Description:

THINNER SH is characterized as an organic compound having a single hydroxyl group. It is manufactured as a solvent for shellac.

Characteristics and Physical Properties:

Appearance	Visual	Clear & Bright
Specific weight	ASTM D 4052	0.789 kg/L
Colour (Saybolt)	ASTM D 1209	LT 5
IBP	ASTM D 1078	78.2°C
Acidity	ASTM D 1613	0.0018 %
Water content	ASTM E 1064	0.04 %
Suspended matter	Visual	nil
Water solubility	ASTM D 1722	Miscible
Purity	GC	99.9 %
Methanol	GC	<0.01
n-Propanol	GC	<0.01
Aromatic hydrocarbon	GC	<0.01

Note:

The contents of the aforementioned containers are of industrial use only by professionals.

Storage:

Keep the container tightly closed. Shelf life is unlimited in close container. Keep away from direct sunlight and other sources of heat or ignition

Packing:

Available in USG, 18 lit (Pail) and 200 lit (Drum)

Physiological Hazards:

THINNER SH contains highly flammable solvents. Harmful if inhaled and if absorbed through skin can cause irritation. Always use protective gloves and eye goggles when handling this product. It is highly recommended to provide proper ventilation on working area. Keep out of reach of children. If contact with skin or splash in eyes, wash with fresh water for a couple of minutes while removing contaminated clothing and shoes. If affected by inhalation of vapour, remove to fresh air. If swallowed, call a physician immediately. Do not induce vomiting.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.