

APEL SILICONE

1. PRODUCT DESCRIPTION

Trade Name: Apel Silicone

Product Description: Apel silicone is one component (acetic curing) silicone sealant for range of general sealing and glazing applications.

2. TECHNICAL DATA

Appearance: Paste

Colour: White, Transparent, Black

Odor: Acetic acid

Tack-Free Time: 20 min.

Viscosity: ~ 800.000 mPa.s

Density 25°C: 0,90-1,00 g/cm³

Solubility in water: Not soluble

3. APPLICATIONS

It provides strong adhesion for nonporous materials including glass, woodwork, metal, tile, PVC and general construction materials.

4. INSTRUCTIONS

Clean application place (dry and free of grease and dust).

Mask joint edges with adhesive tape.

Cut to open cartridge screw nozzle on cartridge and cut of tip at desired angle.

Insert cartridge in gun.

Smooth silicone with water after application . Remove masking tape.

5. PACKAGING

It is presented in 250ml/280g and 280ml/320g plastic cartridges.

6. STORAGE AND SHELF LIFE

Shelf life is 1 year after the production date if stored in its original package between 5°C to 30°C.

7. WARNINGS/ SAFETY PRECAUTIONS

Protect from sunlight and freezing .

Wear any liquid-tight rubber or vinyl gloves.

Consult Material Safety Data Sheet for further information.