



**LEVASSEUR**  
*Your paint expert*

# EASY COLOR ACRYL VARNISH

## WATER BASE

### PRODUCT DESCRIPTION

High gloss waterbased clear coat.  
Gloss level : 87%  
Rhopoint : 60°.

### PROPERTIES

Very resistant to water and mechanical wear.  
Very good weather resistant outside  
Support has to be prepared according the DIN 18363 Teil c norm.  
Apply 2 layers of clear coat respecting 12h waiting time between the layers to obtain a maximum result.

### SUBSTRATES

Can be applied over any waterbased or solvent based paint.  
If you need to apply this clear coat over an epoxy or PU paint a drying time of more then 72h has to be respect.  
In this case the surface has to be sand (P400) before application for a better adhesion.  
This product can also be applied on non ferro metal like inox, galvanized steel or aluminium.  
Can also be applied on wood panels (mdf) or natural wood.  
Has no UV protection for outside.  
Can not be applied on ferro metals.

### APPLICATION

Application : Brush roller and spray gun.  
Dilution : 2% when applied with brush or roller, 5-10% with spray gun.  
For spray gun :  
Nossle : 1,3 à 1,6 mm  
Pressure : 1.5 à 2.5 bar  
Apply 40 microns dry  
Viscosity : 30 to 40 sec.  
DIN 4 mm / 20°C

### PROPERTIES

Density : 0.93 Kg/L  
Viscosity : 1200cp (Haake rotor n°1 – 22°C)  
Drying : 2 hours  
Consumption : 12-14m<sup>2</sup>/L according to the substrate  
VOC : 9g/L

---

#### S.A. LEVASSEUR NEWCO N.V.

Rue du Bourdon - 121 - Horzelstraat - B - 1180 BRUXELLES - BRUSSEL  
Tel. 02/ 376 00 18 – Fax. 02/ 376 38 86 – [info@g-levasseur.com](mailto:info@g-levasseur.com) – [www.g-levasseur.com](http://www.g-levasseur.com)



**LEVASSEUR**  
*Your paint expert*

## CLEANING

Water.

## STORAGE CONDITIONS

1 year in closed sealed cans. Stock in a ventilated area with temperature between 5°C and 30°C.

*Our information on the technical product is used only as assistance to professional workers. During the implementation of our products, we always advise to start with a test on a small area.*

---

**S.A. LEVASSEUR NEWCO N.V.**

Rue du Bourdon - 121 - Horzelstraat - B - 1180 BRUXELLES - BRUSSEL  
Tel. 02/ 376 00 18 – Fax. 02/ 376 38 86 – [info@g-levasseur.com](mailto:info@g-levasseur.com) – [www.g-levasseur.com](http://www.g-levasseur.com)