



COPRABEL
Quality in Colors

COPRABEL S.A Z.I. Wavre-Nord, Avenue Lavoisier, 7
BE-1300 Wavre Belgium
Tel: +32 10 23 82 80 Fax: +32 10 23 82 89
www.coprabel.com info@coprabel.com



TECHNICAL DATA SHEET

EASY COLOR® TEAK OIL

DESCRIPTION

EASY COLOR® TEAK OIL is designed to protect, nourish and embellish new and old woods. It avoids graying effect and protects against water and other problems caused by environmental agents. This impregnation product for exotic woods is suitable for both indoor and outdoor works.

PRECAUTIONS

- Mix carefully before use.
- Avoid contact with eyes and skin.
- Wear protective clothes, glasses and gloves.
- Keep out of reach of children.
- Keep products away from frost and from heat sources.
- Do not dispose of residual paint by flushing it away.
- Take appropriate precaution when disposing of the packages.
- Consult the Safety Data Sheet for more details.

METHOD OF USE

Surface preparation	Make sure the wood is healthy, clean and dry (remove all traces of previous protection, detergent residues or other contaminations).
Application	Apply one coat of EASY COLOR® TEAK OIL using a brush designed for stains or a cloth. After 15 minutes, remove all exceeding oil with a dry and clean cloth. If necessary, after 24h, apply a second coat of EASY COLOR® TEAK OIL.
Drying time	At 20°C and 60% HR. Dust free: 8 hours. Complete: after 24 hours.
Cleaning of the material	With white-spirit right after use.
Shelf life	24 months.



COPRABEL
Quality in Colors

COPRABEL S.A Z.I. Wavre-Nord, Avenue Lavoisier, 7
BE-1300 Wavre Belgium
Tel: +32 10 23 82 80 Fax: +32 10 23 82 89
www.coprabel.com info@coprabel.com



TECHNICAL DATA SHEET

EASY COLOR® TEAK OIL

TECHNICAL SPECIFICATIONS

Solid content	0 % by weight.
Density at 20°C	0,85 g/cm ³ .
Flash Point	35°C.
Coverage	5-10 m ² /L (depending on the type of the substrate).
Color	Colorless.
Packaging	1 L & 5 L (other packaging on demand).

REMARKS AND RECOMMENDATIONS

Store in a well-ventilated and dry room at temperatures between 5°C and 35°C. Protect from heat and direct sunlight. Keep container tightly closed. Store carefully closed containers upright to prevent any leaks.

Good ventilation is required in confined areas to ensure correct drying.

Warranty invalid, if other system than provided by COPRABEL S.A. is used.

Note: Cancels and replaces the former editions. It's up to our customers to check, before application, if it is indeed the latest edition. The information contained in this note has only one indicative range and cannot compensate a description suitable with the nature and the state of surface to be treated.