

TECHNICAL DATA SHEET MITREAPEL INSTANT ADHESIVE FLEX

Release date: 11.12.2018 Revision Date/No: -/ Rev.00 TDS No: TDS 121-EN

1. PRODUCT DESCRIPTION

Trade Name: Mitreapel Instant Adhesive Flex

Product Description: Cyanoacrylate Based Elasticized Instant Adhesive

2. TECHNICAL DATA

Appearance: Liquid

Colour: Clear, colorless

Odour: Sharp, characteristic

Density: 1,05 g/cm³

Flash Point: 85°C

Viscosity: 1.200-1.500 mPa.s

3. APPLICATIONS

In addition to the standard fast adhesive properties, the vibration resistance is increased. Gives instant bonding for laminates, woods, foils, MDF, leather, massive and metal surfaces. It has a perfect gap filling properties.

4. INSTRUCTIONS

It can be use two different ways. Using with one component, apply glue on one surface than stick peaces together. Wait for glue to dry.

Using with two components, apply activator on one surface and wait for activator steam to vanish. Apply glue to the other surface then stick peaces together. Wait at least 12 seconds glue to dry.

5. PACKAGING

It is presented for one component 100 g , for two components 100 g+400 ml in plastic bottles.



TECHNICAL DATA SHEET MITREAPEL INSTANT ADHESIVE FLEX

Release date: 11.12.2018 Revision Date/No: -/ Rev.00 TDS No: TDS 121-EN

6. STORAGE AND SHELF LIFE

Keep away from sunlight and store between 5-25°C. (Optimum storage temperature is 5°C) If stored in proper conditions shelf life is 1 year.

7. WARNINGS/ SAFETY PRECAUTIONS

Wear protective clothing and gloves while working. Keep children away. Provide ventilation.

Do not burn or drill the can.

Protect from direct sunlight and keep off temperatures above 40°C. Keep away from igniting sources. Do not smoke.

Consult Material Safety Data Sheet for further information.