



# SYNTHETIC GLOSS WHITE

## General Description:

SYNTHETIC GLOSS WHITE is a finished coat based on synthetic resin used as a gloss finish in alkyd system.

## Advantages:

- For interior and exterior surfaces like masonry, steel, wood, asbestos etc.
- Weather resistance and exterior protection.
- Good colour retention.
- Ease of application.
- Excellent for wood and metal surfaces.
- Good hiding power and adhesion.
- Super glossy finish.

## Characteristics and Physical Properties:

Colour	As per RAL colour card
Coverage	11 – 13 m <sup>2</sup> / lit.
Flash Point	39 <sup>o</sup> C
Solid Content	Approx 50% by volume
DFT	35 microns per coat.

## Drying Time:

Touch Dry	After 4 hrs.
Over coating	min. 16 hrs.
Shelf Life	One (1) year

## Application procedure:

- Substrate must be free from oil and other contaminants.

- Sandblasting is required to Sa 2 ½, if sandblasting is not possible, manual wire brushing is recommended. Use Deruster to remove away rust and rinse with water and let it dry. Apply 1- 2 coats of red oxide primer by roller, brush or spray or 1 – 2 coats of under coat prior to the application of SYNTHETIC GLOSS WHITE.

## Storage:

SYNTHETIC GLOSS WHITE should be kept in a cool area below 25<sup>o</sup>C. Keep in tightly closed container.

## Cleaning of Tools:

All tools should be cleaned with Wash Thinner as soon as possible.

## Packing:

Available in LTR and 1USG.

## Physiological Hazards:

SYNTHETIC GLOSS WHITE does not contain dangerous solvents, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment. SYNTHETIC GLOSS WHITE is flammable and harmful if swallowed. If contact with eyes or skin occurs, wash well with fresh water and seek immediate medical advise.